

ACTIVSLATEXR

PRODUCT SPECIFICATIONS – ACTIVSLATEXR

What's in the Box

Activslate
Activpen (1)
Pen Holder (user installable)
Serial Cable, Power Cables (AC adapter and power cable) for recharging
Quick Start Guide

ActivslateXR

Resolution internal 1000 dots per inch
Output rate 75 coordinates pairs per second
Pointing device Cordless battery-free pen (Activpen); 5 mm working pen proximity
Digitizing technology Passive electromagnetic interface encased for technical reliability and durability
Connection & Usability Built-in RF connectivity (915 MHz) to Activboard, optional Transceiver for Activboard 75, or Activhub. Maximum of 64 Activslates per receiver REQUIRES one of these transceivers and either Activstudio or Activprimary to operate.
RF Channels 3, user selectable; 99 IDs for up to 297 configurations
LCD Interface Allows for customizing tablet name, contrast, auto-sleep time; shows battery life remaining and identification. Interactive to allow for registering with receiver.
Range Up to 50 ft.
Certification CE, FCC, UL listed
Operating temperatures 36 F to 113 F (2 C to 45 C)
Battery Technology Rechargeable Lithium Ion
Battery Life 24 hours with constant use (Typical usage: 3 hours per day would require charging once every 2 months)
Charge Time Approximately 3 hours
Overall dimensions 13.4" x 9.4" (340 x 238mm)
Active area dimensions 8" x 6" (200 x 150mm)
Active area diagonal 10" (250mm)
Packed weight 3.5lbs (1.6kg)
Tablet weight 1.4lbs (0.620kg)
Warranty 1 year

Activpen

Overall dimensions 6" x 0.6" diameter (155 x 16mm diameter)
Weight 0.5oz (15.3g)
Features Left mouse click on the tip, right click on the barrel. Ergonomic design, battery-free, tapered tip
Warranty 1 year

ACTIVSLATEXR

PRODUCT SPECIFICATIONS – ACTIVSLATEXR

Computer Requirements

Windows

Macintosh

Operation of Activboard requires installation of driver found on Activstudio or Activprimary application CD. The most current driver can be found on the US Promethean website. User with administrator/privileged access rights required to install driver and software.

Recommended: PC with Intel PIII--1 Ghz or higher (or equivalent), 256 MB RAM, 32 MB graphics card, DirectX9 (included on application CD), CD Rom drive, microphone, and sound card. Windows 98, 2000/XP, NT, or ME.

Macintosh minimum: Mac OS 10.2.8, 128 MB Ram, 8 MB VRAM, G3 350 Mhz Processor, 800 x 600, 700 MB of free disk space for full installation. **Macintosh preferred:** Mac OS 10.4, 256 MB Ram, 32 MB VRAM, G4 466 Mhz Processor, 1024 x 768, 700 MB free disk space for full installation. Spotlight search requires Mac OS 10.4 or higher.

Support and Training Options

- ✓ User and Training Guides for components of the Activclassroom are included on the application CDs, as well as the US Promethean website.
- ✓ To Access free on-line lessons for both Activstudio and Activprimary go to www.atomiclearning.com.
- ✓ Become a member of Promethean Planet at www.prometheanplanet.com (on-line tutorials, user forum, additional lessons, ideas from other users).
- ✓ On-site training options for Activstudio are also available by contacting your Promethean representative.

Product Image



ACTIVSLATEXR

PRODUCT SPECIFICATIONS – ACTIVSLATEXR

Promethean Part Numbers

ActivslateXR – 1-PRM-RS1-01-US2 (for use with all boards with built-in radio: 78, 64, 50)

ActivslateXR Upgrade Kit – 1-PRM-RS1-UPG-US2 (for use with all boards without built-in radio--includes separate RF transceiver to attach to those boards: 75, 60 and 48)

*Activboard 95 requires the Activboard 95 Upgrade Kit (Activote 32, Activslate and Activhub) in order to use the Activslate: 1-PRM-AB95B-UPG-US.

PROMETHEAN, INC.

1165 SANCTUARY PARKWAY, STE 400
ALPHARETTA, GA 30004

WWW.PROMETHEANWORLD.COM

SALES AND SUPPORT: 888-652-2848

Last revised 11/28/06

